

# Atlassian Bitbucket Integrations

## Introduction

The Bitbucket integration collects audit logs from the audit log files or the [audit API](#).

Reference: <https://developer.atlassian.com/server/bitbucket/reference/rest-api/>

## Assumptions

The procedures described in Section 3 assume that a Log Collector has already been set up.

## Requirements

For more information on auditing in Bitbucket and how it can be configured, see [View and configure the audit log](#) on Atlassian's website.

Reference: <https://confluence.atlassian.com/bitbucketserver/view-and-configure-the-audit-log-776640417.html>

## Logs

### Audit

The Confluence integration collects audit logs from the audit log files or the audit API from self-hosted Confluence Data Center. It has been tested with Confluence 7.14.2 but is expected to work with newer versions. As of version 1.2.0, this integration added experimental support for Atlassian Confluence Cloud. JIRA Cloud only supports Basic Auth using username and a Personal Access Token.

## Atlassian Bitbucket Integration Procedures

Please provide the following information to CyTech:

### **Collect Bitbucket audit logs via log files**

1. Path
2. Preserve Original Event? (Enable Yes/No)
  - Preserves a raw copy of the original event, added to the field event.original
3. Tags
4. Processors (Optional)
5. Processors are used to reduce the number of fields in the exported event or to enhance the event with metadata. This executes in the agent before the logs are parsed.
6. Indexing settings (experimental) (Enable Yes/No)
7. Select data streams to configure indexing options. This is an experimental feature and may have effects on other properties.

### **Collect Bitbucket audit logs via API (Enable Yes/No)**

1. API URL - The API URL without the path.
2. Bitbucket Username - JIRA Username. Needs to be used with a Password. Do not fill if you are using a personal access token.
3. Bitbucket Password - JIRA Password. Needs to be used with a Username. Do not fill if you are using a personal access token.
4. Personal Access Token - The Personal Access Token. If set, Username and Password will be ignored.
5. Initial Interval - Initial interval for the first API call. Defaults to 24 hours.

---

Revision #2

Created 23 April 2024 10:32:07

Updated 19 June 2024 06:54:01